



Dreadnought Tile

Generated on 08.10.2017

Detailed description

Dreadnought Tile is a 11 mm thick bitumen backed 500 x 500 mm tile manufactured with 90% polypropylene and 10% recycled polyester. It is designed for use as an entrance flooring finish.

Laying:

- Recommended carpet layout - the method of installation should conform to BS5325.
- For details of subfloor preparation and a full guide to installation visit manufacturer's website.
- Before laying Dreadnought tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
- Dreadnought tiles should be laid rotationally, alternating the direction of the tiles through 90°.

Adhesive Guide:

For tiles use F.Ball F41 or Bostick Laybond Carpet Tile Tackifier.

Product guidance - As Standard

Type:

Fibre bonded entrance area carpet tile.

Size:

500 x 500 mm.

Thickness:

11 mm.

Weight:

3994 g/m².

Colour Fastness:

- Light (BS EN ISO 105:B02) >6.
- Wet Rubbing (BS EN ISO 105:B01) 4-5.
- Dry Rubbing (BS EN ISO 105:X12) 4-5.

Options

Colour:

Available in 6 standard colourways.

Heckmondwike FB



Heckmondwike FB

Wellington Mills
Liversedge
West Yorkshire
WF15 7FH

Tel: +44 (0)1924 406161

www.heckmondwike-fb.co.uk
sales@heckmondwike-fb.co.uk



Product specification

Manufacturer

- Name: Heckmondwike FB
- Web: www.heckmondwike-fb.co.uk
- Email: sales@heckmondwike-fb.co.uk
- Tel: +44 (0)1924 406161
- Fax: +44 (0)800 136769
- Address: Wellington Mills, Liversedge, West Yorkshire WF15 7FH

Product reference Dreadnought Tile

Colour
Anthracite
Ash Grey
Fiesta
Indigo
Lincoln green
Slate