



Dreadnought UB

Generated on 08.10.2017

Detailed description

Dreadnought UB is an 11 mm thick sheet clean-off carpet, manufactured with 90% polypropylene and 10% recycled polyester. The 2 m wide carpet is designed for use in most building entrance situations.

Laying:

- Recommended carpet layout - the method of installation should conform to BS5325.
- For details of subfloor preparation and a full guide to installation visit manufacturer's website.

Adhesive Guide:

Sheet carpet should be fully adhered with F Balls F3 or F52 or Bostik Laybond carpet adhesive.

Product guidance - As Standard

Type:

Fibre bonded entrance area carpet.

Thickness:

11 mm.

Width:

2.00 m.

Weight:

1494 g/m².

Colour Fastness:

- Light (BS EN ISO 105:B02) >6.
- Wet Rubbing (BS EN ISO 105:B01) 5.
- Dry Rubbing (BS EN ISO 105:X12) 5.

Options

Colour:

Available in 6 standard colourways.

Product specification

Manufacturer

Heckmondwike FB



Heckmondwike FB

Wellington Mills
Liversedge
West Yorkshire
WF15 7FH

Tel: +44 (0)1924 406161

www.heckmondwike-fb.co.uk
sales@heckmondwike-fb.co.uk



- Name: Heckmondwike FB
- Web: www.heckmondwike-fb.co.uk
- Email: sales@heckmondwike-fb.co.uk
- Tel: +44 (0)1924 406161
- Fax: +44 (0)800 136769
- Address: Wellington Mills, Liversedge, West Yorkshire WF15 7FH

Product reference Dreadnought

Colour
Anthracite
Ash grey
Fiesta
Indigo
Lincoln green
Slate