



Hippo

Generated on 08.10.2017

Detailed description

Hippo is a 12 mm thick sheet clean-off carpet, manufactured with 90% polypropylene and 10% recycled polyester. The 2 m and 4 m wide carpet is designed for use in building entrance situations.

Laying:

- Recommended carpet layout - the method of installation should conform to BS5325.
- For details of subfloor preparation and a full guide to installation visit manufacturer's website.

Adhesive Guide:

Sheet carpet should be fully adhered with F Balls F3 or Bostik Laybond carpet adhesive. Sheet carpets can be laid into F40 as a release system.

Product guidance - As Standard

Type:

Fibre bonded entrance area carpet with a rubber waffle backing.

Thickness:

12 mm.

Weight:

2379 g/m².

Colour Fastness:

- Light (BS EN ISO 105:B02) >6.
- Wet Rubbing (BS EN ISO 105:B01) 4-5.
- Dry Rubbing (BS EN ISO 105:X12) 4-5.

Options

Colour:

Available in 8 standard colourways.

Product specification

Manufacturer

- Name: Heckmondwike FB
- Web: www.heckmondwike-fb.co.uk

Heckmondwike FB



Heckmondwike FB
Wellington Mills
Liversedge
West Yorkshire
WF15 7FH

Tel: +44 (0)1924 406161

www.heckmondwike-fb.co.uk
sales@heckmondwike-fb.co.uk



- Email: sales@heckmondwike-fb.co.uk
- Tel: +44 (0)1924 406161
- Fax: +44 (0)800 136769
- Address: Wellington Mills, Liversedge, West Yorkshire WF15 7FH

Product reference Hippo
Width 2.00 m
4.00 m
Colour Anthracite
Ash Grey
Blue
Brown
Indigo
Heath
Pebble
Slate