



Supacord Tile

Generated on 08.10.2017

Detailed description

Supacord Tile is a 7.6 mm thick bitumen backed 500 x 500 mm tile manufactured with 80% polypropylene, 15% polyamide and 5% recycled polyester. It is designed for use in most building situations, including computer rooms.

Laying:

- Recommended carpet layout - the method of installation should conform to BS5325.
- For details of subfloor preparation and a full guide to installation visit manufacturer's website.
- Before laying Supacord tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
- Supacord tiles should be laid rotationally, alternating the direction of the tiles through 90°.

Adhesive Guide:

For tiles use F.Ball F41 or Bostick Laybond Carpet Tile Tackifier.

Product guidance - As Standard

Type:

Fibre bonded thin ribbed carpet tile.

Size:

500 x 500 mm.

Thickness:

7.60 mm.

Weight:

4020 g/m².

Colour Fastness:

- Light (BS EN ISO 105:B02) >6.
- Wet Rubbing (BS EN ISO 105:B01) 4-5.
- Dry Rubbing (BS EN ISO 105:X12) 4-5.

Options

Colour:

Available in 42 standard colourways.

Heckmondwike FB



Heckmondwike FB

Wellington Mills
Liversedge
West Yorkshire
WF15 7FH

Tel: +44 (0)1924 406161

www.heckmondwike-fb.co.uk
sales@heckmondwike-fb.co.uk



Product specification

Manufacturer

- Name: Heckmondwike FB
- Web: www.heckmondwike-fb.co.uk
- Email: sales@heckmondwike-fb.co.uk
- Tel: +44 (0)1924 406161
- Fax: +44 (0)800 136769
- Address: Wellington Mills, Liversedge, West Yorkshire WF15 7FH

Product reference Supacord Tile

Colour

Acorn
Amethyst
Anthracite
Aquamarine
Arctic Blue
Astra Blue
Azure
Blue
Blue Moon
Blueberry
Claret
Cobalt
Damson
Emerald
Flint
Graphite
Green
Gunmetal
Heather
Indigo
Kingfisher
Kingston Grey
Lavender
Magenta
Moonlight
Moorland
Mulberry
Onyx
Opal
Orange
Pacific Blue
Pale Olive
Purple
Pebble
Red
Safari
Seal
Sherwood
Steel Grey
Violet



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

Willow
Yellow