



## Wellington Velour Tile

Generated on 08.10.2017

### Detailed description

Wellington Velour Tile is a 11.2 mm thick bitumen backed 500 x 500 mm tile manufactured with 90% polypropylene and 10% recycled polyester. It is designed for use in most building situations, including computer rooms.

### Laying:

- Recommended carpet layout - the method of installation should conform to BS5325.
- For details of subfloor preparation and a full guide to installation visit manufacturer's website.
- Before laying Wellington tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
- Wellington tiles should be laid rotationally, alternating the direction of the tiles through 90°.

### Adhesive Guide:

For tiles use F.Ball F41 or Bostick Laybond Carpet Tile Tackifier.

### Product guidance - As Standard

#### Type:

Fibre bonded velour carpet tile.

#### Size:

500 x 500 mm.

#### Thickness:

11.2 mm.

#### Weight:

4180 g/m<sup>2</sup>.

#### Colour Fastness:

- Light (BS EN ISO 105:B02) >6.
- Wet Rubbing (BS EN ISO 105:B01) 5.
- Dry Rubbing (BS EN ISO 105:X12) 5.

### Options

#### Colour:

Available in 4 standard colourways.

Heckmondwike FB



#### Heckmondwike FB

Wellington Mills  
Liversedge  
West Yorkshire  
WF15 7FH

Tel: +44 (0)1924 406161

[www.heckmondwike-fb.co.uk](http://www.heckmondwike-fb.co.uk)  
[sales@heckmondwike-fb.co.uk](mailto:sales@heckmondwike-fb.co.uk)



## Product specification

### Manufacturer

- Name: Heckmondwike FB
- Web: [www.heckmondwike-fb.co.uk](http://www.heckmondwike-fb.co.uk)
- Email: [sales@heckmondwike-fb.co.uk](mailto:sales@heckmondwike-fb.co.uk)
- Tel: +44 (0)1924 406161
- Fax: +44 (0)800 136769
- Address: Wellington Mills, Liversedge, West Yorkshire WF15 7FH

**Product reference** Wellington Velour Tile

**Colour**  
Charcoal  
Dove Grey  
Marine  
Moonstone