










# DIAMOND

ENTRANCE & TRANSITION AREA RANGE

 **MADE IN THE UK. MADE TO LAST.**

## Specification

<b>PRODUCT</b>	Diamond Heavy Contract Fibre Bonded Carpet and Tiles	
<b>FIBRE CONSTRUCTION</b>	85% Polypropylene, 15% Recycled Polyester	
<b>WEIGHT</b>	2500gsm (Sheet), 4400gsm (Tile)	
<b>THICKNESS</b>	10.50mm (Sheet), 11mm (Tile)	
<b>ROLL WIDTH</b>		2 metre (Rubber Crumb backing)
<b>TILE SIZE</b>		50cm x 50cm (Tiles are Bitumen backed)
<b>TILES PER BOX</b>	16 (4m <sup>2</sup> )	
<b>COLOUR FASTNESS</b>	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:BO1) 5 Dry Rubbing (BS EN ISO 105:X12) 5	
<b>FLAMMABILITY</b>	(BS6307) Methenamine Pill Test - Pass	
<b>BS EN 13501</b>	Class Efl (Sheet) Class Efl (Tile)	
<b>INSTALLATION</b>	 Tiles	Diamond tiles should be laid tessellated as per the icon provided. The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit: <a href="http://www.heckmondwike-fb.co.uk">www.heckmondwike-fb.co.uk</a> . Before laying Diamond, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
<b>ADHESIVE GUIDE</b>	Sheet carpet should be fully adhered with F. Ball F3 or Bostik Laybond Carpet Adhesive. For tiles use F. Ball F41 Tackifier or Bostik Laybond Carpet Tile Tackifier.	
<b>MAINTENANCE</b>	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: <a href="http://www.heckmondwike-fb.co.uk">www.heckmondwike-fb.co.uk</a>	

 EN 14041 Heckmondwike FB Liversedge WF15 7FH 09 Diamond Sheet Fibre Bonded Sheet Floorcovering intended for internal use  	 EN 14041 Heckmondwike FB Liversedge WF15 7FH 09 Diamond Tile Fibre Bonded Tile Floorcovering intended for internal use  
--	--



PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.